

120, 140 and 145 crimping machines

The brand new 120 and 140 crimping machines extend the range of Lillbacka Powerco's new generation crimping machines. They are unbeaten in terms of speed, precision, durability and quality.



120 UC with C1 control unit

UC CONTROL

The most advanced crimping control in the world. Basic functions quick and easy to use. Extends up to the online quality monitoring.

- online quality monitoring
- connectivity
- usability

Lillbacka Powerco Ltd
 P. O. Box 1, FI-62301 Härmä, Finland
 Tel. +358 6 485 4444, Fax +358 6 485 4400
 powerco@lillbacka.com
 www.lillbacka.com/powerco

FLEXIBLE LAYOUT

- separate hydraulic- and crimping units for optimal use of space
- optional connection kit

ALL-ROUND USE

- front, back and side
- operating unit with free placing

SIDE MOUNTING TRACK

- for die set racks, side tables, etc.
- customer's own accessories

SERVICE-FRIENDLY CONSTRUCTION

- all-round and quick accessibility for maintenance

ENERGY SAVING MODE

- motor stand-by function
- silent

OPTIONS

- pressure crimping
- multi-step crimping
- online quality monitoring
 - auto greasing
 - foot pedal
 - side table
 - die set racks
 - connection kit
- speed adjustment
 - oil cooler
- pinning support mandrel

Technical specifications

Technical specifications	120	120S	140	140S	145
Crimping range Ø (mm)	10... 87	10... 87	10... 124	10... 124	10... 124
Crimping force (kN)	2800	2800	3200	3200	3500
Number of crimps/hour ⁽⁴⁾	2400	3000	2000	2500	2400
Hose size ID (inch)	2	2	2½	2½	2½
Die type ⁽¹⁾	32	32	32/FP140	32/FP140	32/FP140
Max opening (mm) ⁽²⁾	+68	+68	+82	+82	+82
Master die shoe length (mm)	97	97	97	97	116
Motor (kW)	5.5	7.5	5.5	7.5	7.5
Dimensions / crimping unit					
length (mm)	1063	1063	1063	1063	1063
width (mm)	737	737	737	737	756
height (mm)	1589	1589	1589	1589	1589
Dimensions / hydraulic unit					
length (mm)	713	713	713	713	713
width (mm)	705	705	705	705	705
height (mm)	1059	1059	1059	1059	1059
Weight (kg) / crimping unit	845	895	875	925	875
Weight without oil (kg) / hydraulic unit	182	182	182	182	182

(1) see table for standard die set data;

(2) min. crimping dia of die set added by table value

(3) industrial hose

(4) theoretical with ½" hose ΔØ 10 mm

Subject to changes without prior notice.

Standard die sets for 120 and for 140 used with adapter dies

Code	Crimping diameter (mm)	L (mm)
32-10	10.0 - 12.0	55
32-12	12.0 - 14.0	55
32-14	14.0 - 16.0	55
32-16	16.0 - 19.0	55
32-19	19.0 - 22.0	55
32-22	22.0 - 26.0	70
32-26	26.0 - 30.0	70
32-30	30.0 - 34.0	70
32-34	34.0 - 39.0	75
32-39	39.0 - 45.0	75
32-45	45.0 - 51.0	90
32-51	51.0 - 57.0	90
32-57	57.0 - 63.0	100
32-63	63.0 - 69.0	110
32-69	69.0 - 75.0	110
32-74	74.0 - 80.0	110
32-78	78.0 - 87.0	110

In addition to the standard die sets, a special die sets are available according to customer's request.

Standard die sets for 145 used with adapter dies

Code	Crimping diameter (mm)	L (mm)
32-10	10.0 - 12.0	55
32-12	12.0 - 14.0	55
32-14	14.0 - 16.0	55
32-16	16.0 - 19.0	55
32-19	19.0 - 22.0	55
32-22	22.0 - 26.0	70
32-26	26.0 - 30.0	70
32-30	30.0 - 34.0	70
32-34	34.0 - 39.0	75
32-39	39.0 - 45.0	75
32-45	45.0 - 51.0	90
32-51	51.0 - 57.0	90
32-57	57.0 - 63.0	100
32-63L	63.0 - 69.0	120
32-69L	69.0 - 75.0	120
32-74L	74.0 - 80.0	120
32-78L	78.0 - 87.0	120

In addition to the FP145 die sets a wide range of special die sets is available.

FP140 die sets for 140 model used without adapter dies

Code	Crimping diameter (mm)	L (mm)
140-84	84.0 - 92.0	110
140-92	92.0 - 100.0	110
140-100	100.0 - 108.0	110
140-108	108.0 - 116.0	110
140-116	116.0 - 124.0	110

FP140 die sets for 145 model used without adapter dies

Code	Crimping diameter (mm)	L (mm)
140-84L	84.0 - 92.0	120
140-92L	92.0 - 100.0	120
140-100L	100.0 - 108.0	120
140-108L	108.0 - 116.0	120
140-116L	116.0 - 124.0	120

In addition to the FP140 die sets a wide range of special die sets is available.